

Keestrack

TECHNICAL SPECIFICATIONS	
Capacity up to	251 kW, 350 kVA
Weight	9 t
Drop Off - Drop On module, can be placed on top of e-drive crushers,	•
besides the machine or on the tracked platform	
Standard 450 l / 118 gal fuel tank	•
Track-unit: Length, total width, track shoe width	3314, 2500, 400 mm
2-speed track drive	1,1 km/h and 2 km/h
Engine unit(s)	251 kW, 350 kVA
"Power plug out:	
POWER LOCK plug-out 3 Phases, 400V;	
50 Hz; 450 kVA (660 A)	•
Plug out 3 Phases, 400V; 50 Hz, 32 A	
Plug-out 3 Phases, 400V; 50 Hz, 63 A"	
Control	PLC – IP 67 LCD screen 4,3" & remote control
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	electric plug out
ZERO drive (no combustion engine, plug-in electric)	electric plug out

<u>OPTIONS</u>

Additional 2000 l fuel tank placed on platform for more autonomy	•
Radio remote	•
Working lights	•
Plug-in connections, 3 phases+ E, 660 A Powerlock & 25 m cable	•

TRANSPORT	
Transport l x w x h (mm)	6300 x 2500 x 2650 mm

	LEGENDA
applicable - available	•
not applicable- not available	1





